

„CATERPILLAR” FIBREGLASS TANKS AND SEPTIC TANKS

Light laminated rainwater tanks and three-chamber septic tanks

UNDER NORMAL CONDITIONS NO BASE OR CONCRETE ENCASEMENT IS REQUIRED

Further static fitting is necessary in the following cases:

- › The area over the tank or in its vicinity should be rolling
- › The tank's depth is under 0.5 m (from the tank ceiling)
- › Groundwater is present in the tank position

HIGH SOLIDITY OF THE TANK SHELL

- › When placed in depth, it sustains long-term evacuation

THERMAL AND UV STABILITY

- › Surface position is possible

LOW WEIGHT

- › Even larger tanks can be positioned manually when a few people are involved



VODACZ

„CATERPILLAR” LAMINATED TANK DIMENSIONS

Order Code	Name	DN	Duct height (m)	Duct Ø (m)	Tank Ø (m)	Tank length (m)	Weight (kg)
LAM 2	Caterpillar 2.000	100	0.40	0.40	1.25	2.50	70
LAM 3	Caterpillar 3.000	Supply DN 150	0.60	0.40	1.45	2.50	100
LAM 4	Caterpillar 4.000		0.60	0.40	1.80	2.50	140
LAM 6	Caterpillar 6.000		0.60	0.40	1.80	3.50	192
LAM 8	Caterpillar 8.000		0.60	0.40	1.80	4.30	245
LAM 11	Caterpillar 11.000		0.60	0.40	1.80	6.10	340
LAM 14	Caterpillar 14.000		0.60	0.40	2.50	3.90	500
LAM 18	Caterpillar 18.000		0.60	0.40	2.50	4.85	660
LAM 22	Caterpillar 22.000		0.60	0.40	2.50	5.75	820
LAM 26	Caterpillar 26.000		0.60	0.40	2.50	6.70	980
LAM 30	Caterpillar 30.000		0.60	0.40	2.50	7.60	1,140
LAM (N80)	Duct head		400	Head height 0.8 m			
LAM (N120)	Duct head	400	Head height 1.2 m				
LAM (N80)	Duct head	600	Head height 0.8 m				

*upon request, laminated tanks can be made with Ø 600 mm inlet hole.

Upon request, we provide also LAM 1.3 (1,300 l volume) and LAM 2.6 (2,600 l volume).

„CATERPILLAR” BIOLOGICAL SEPTIC TANK DIMENSIONS

Order Code	Name	DN	Duct height (m)	Duct Ø (m)	Tank Ø (m)	Tank length (m)	Weight (kg)
LAMSEP 4	Caterpillar Septic Tank 2-4EO (3 m³)	100	0.40	0.35	1.25	2.50	125
LAMSEP 6	Caterpillar Septic Tank 4-6EO (4 m³)	150	0.40	0.35	1.80	2.50	180
LAMSEP (N80)	Duct head	Head height 0.8 m					

Upon request, we provide also LAMSEP 2 (2,000 l volume); LAMSEP 2.6 (2,600 l volume); LAMSEP 8 (6,000 l volume) and LAMSEP 10 (8,000 l volume).



Headquarters:
VODA CZ, s. r. o.
 Bohuslava Martinů 1038/20
 500 02 Hradec Králové
 Pražské Předměstí

Plant:
VODA CZ, s. r. o.
 Hořenice 45
 551 01 Jaroměř

Service:

www.vodaczservice.com

Contact:
 e-mail: info@vodacz.com
 Service:
 phone: +420 800 150 155



www.vodacz.com